Data Sheet

| | VA CILKA | |
|---------|----------|--|
| VVE THA | ke sure | |
| | | |
| | | |
| | | |

AMILO Pa 2510-25P

With AMD Turion™64 X2 Mobile Technology cuz:N-NOR-MLVAR001



Issue September 2007



Features

- AMD Turion[™] X2 Mobile Technology TL-50
- 2048MB DDR II 667Mhz (2 x 1024MB), max 2GB
- 250GB Serial ATA HDD
- Dual Layer DVD±R±RW drive (8.5GB)
- 15.4" TFT LCD WXGA display
 - BrilliantView
 - High brightness
 - Resolution of 1280 x 800
- ATI Mobility Radeon® Xpress 1200 graphics with up to 256MB shared memory
- 4-in-1 card reader supports SD/MS/MMC/MSPRO multimedia storage cards.

- 3 x USB 2.0, SPDIF, 2 x Audio, VGA
- WLAN 802.11b/g (54 Mb/s) & 10/100 LAN
- Silent Mode functionality
- Windows® Vista Home Premium FI / SWE / NOR / DK / ENG
- Software included:
 - o Microsoft Works 9.0
 - Microsoft Office Home & Student 60 Day Trial Version
 - Vista DVD Playback Pack
 - Nero 7 Essentials
 - Norman Virus Control 3 years





Operating system

Microsoft® Windows® Vista Home Premium FI / SWE / NOR / DK / ENG

Fujitsu Siemens Computers recommends Microsoft® Windows® Vista Home Premium

Application Software

Microsoft® Works 9.0 Microsoft® Office Home & Student 60 Day Trial Version Vista DVD Playback Pack Nero 7 Essentials Adobe Acrobat Reader Norman Virus Control with 3 years free updates

Quick Start Guide, Manual (on DUDVD), Safety Guide and Warranty Guide

Drivers and Utility Drivers and Utility DVD included. Updates downloadable at: http://www.fujitsu-siemens.com

System, processors, architecture

| Chipset: | AMD M690V + SB600 |
|----------|--------------------------------|
| CPU: | AMD Turion™64 X2 Mobile |
| | Technology TL-50, 1600Mhz |
| | 35W, 512KB L2 Cache, Socket S1 |

Memory

Silent mode Power status Battery status

2048MB DDR II, 2 x 1024MB. Max supported memory 2GB 2 SO-DIMM memory slots (no memory on board)

| Storage devices/drives | | | |
|---|---------------------------------|--|--|
| HDD: | | | |
| 250GB SATA hard disk ODD: | | | |
| · · | urner DL (Double Layer) | | |
| Read speed: CD-ROM 24x, DVD-ROM 8x | | | |
| • | CD-R 24x, CD-RW20x, DVD+R6x, | | |
| • | -R 6x, DVD+RW 4x, DVD-RW 4x, | | |
| DVD | +R DL (Double Layer 8.5GB) 2,4x | | |
| Display | | | |
| 15.4" TFT WXGA, BrilliantView | | | |
| Resolution | 1280 x 800 | | |
| Brightness (typ.) | 180cd/m | | |
| Contrast (typ.) | 300:1 | | |
| ISO 13406-2 class II | | | |
| Graphics | | | |
| ATI Mobility Radeon® Xpress 1200 | | | |
| up to 256MB shared VGA memory | | | |
| Pointing device, keyboard & control buttons | | | |
| Touchpad with a left and right mouse button | | | |
| Full size keyboard with Nordic layout | | | |
| Power button / lid switc | ንት | | |
| Status indicators | | | |
| The notebook has 7 status icons: | | | |
| Caps lock | | | |
| Num lock | | | |
| Media activity (ODD/HDD) | | | |

ACPI functions S1 standby (LCD off) S3 save to RAM S4 save to disk S5 complete off Silent Mode I/O Interfaces 3x USB 2.0 ports 1x VGA, 1x modem, 1x LAN, 1x WLAN 1x ExpressCard slot (34/54mm) 1x line in shared with microphone in 1x headphone out shared with SPDIF 1x power supply 1x 4-in-1 card reader SD/MS/MMC/MSPRO Communications Built-in 56K, V.92 fax modem 10/100Mbps LAN Integrated Wireless LAN (WLAN) solution 802.11b/g: speeds up to 54Mbps Audio Integrated in chipset (7.1 SPDIF), 2 built-in speakers, microphone in shared with stereo in, headphone combined with SPDIF support Launch Keys 2 Launch Keys located on top of the keyboard enabling the user to launch the following applications: Media Player Silent mode (reduce noise level / fan speed by reducing the CPU & VGA performance) Hot Keys The following hotkeys or key combinations are available: Fn-F1 Suspend Fn-F3 Mute Fn-F4 Display toggle, switches display output between display screen and external monitor or dual view Fn-F5 Volume up Fn-F6 Volume down Fn-F7 Increase display brightness Fn-F8 Decrease display brightness Fn-F9 Disable touch pad Power system Li-Ion battery, 6 cell: 10.8 / 11.1V / 4000mAh battery runtime: Approximately 3h depending on usage¹ External AC adapter: 110 - 240V AC, 50 - 60Hz Output: 65 W with 20V DC, 6A Dynamic charge supported ACPI 2.0 supported **Dimensions and weight** Dimension (H x W x D): ~28 - ~36 x 358 x 255mm Weight: 2.8 kg with 6 cell battery² **Operating conditions** Operational: 5°C to 35°C (ambient temperature) 10% to 90% relative humidity, non-condensing

Warranty & Support

Warranty and support according to country terms

1) Battery life may vary depending on product model, configuration, applications, power management settings and features utilized. Recharge time varies depending on usage.

2) Weight may vary depending on actual configuration

Published by

Fujitsu Siemens Computers http://www.fujitsu-siemens.com/ Company stamp

WLAN communication on/off

All rights, including rights created by patent grant or registration of a utility model or design as well as rights of technical modifications are reserved. Delivery subject to availability. Designations may be trademarks, the use of which by third parties for their own purposes may violate the rights of the trademark owners.